

SERIES 7100 • DELUXE Vinyl Casement Window

06/06

PRODUCT INFORMATION SHEET

Series 7100 Nail-On Frame • Series 7190 Retro-Fit Frame
Series 7150 Block Frame

FEATURES

- Fusion welded corners on frame and vents for strength and squareness.
- Dual glazed windows are glazed with 3/4" overall insulating glass with Intercept™ Warm Edge Technology, providing a minimum of 1/2" air space.
- Windows meet and exceeds AAMA/NWWDA 101/I.S. 2-97 specifications for C-30 commercial rating (3060 CL or CR) and R-20 rating, (8050 CO).
- Surpasses California Model Building Security Ordinance for forced entry requirements.
- Frame depth is 2-3/4" overall with a nail-on fin located at 7/8" from the exterior.
- Windows may be stacked (over and under) or mullied (side by side) with other vinyl windows using a unique "Snap-Together" adapter.
- Continuous single finger soft vinyl weather stripping around the frame and vent panel insure air tightness.
- Truth hardware and multipoint locking bars with swing cam latch and hinges are standard. Stainless steel hardware is an available option.
- Screens are mounted on the inside of the window, with special molded screen corners, concealing corner clips.
- Net frame sizes for:
 - Nail-on frame - call out minus 3/8" width and 3/8" height.
 - Block frame - call out minus 1/8" width and 3/8" height.
- Standard and custom sizes available.
- Available in White or Almond color.
- Thermal ratings as tested with CLIMATE SHIELD™ High Performance Low-E glazing: U-Value = .31 and SHCG = .24 (See *Thermal & Optical Ratings* page for more info).

Configuration Available:

CL/CR	=	Single Casement
CC	=	Double Casement
CO/OC	=	Single Casement with Fixed
COC	=	Double Casement with Center Fixed
BCL/BCR	=	Single Bottom Casement with Top Fixed

NOTE: Casements are viewed from exterior. CL represents a single casement hinged on the left side as viewed from the outside looking into the window.