

SERIES 7300 • DELUXE Vinyl Awning Window

06/06

PRODUCT INFORMATION SHEET

**Series 7300 Nail-On Frame • Series 7390 Retro-Fit Frame
Series 7350 Block Frame**

FEATURES

- Frame and vent corners are fusion welded for strength and squareness.
- Windows meet and exceeds AAMA/NWDA 101/I.S. 2-97 specifications for R-25 residential rating. (4⁰ X 8⁰ BA with a 3⁰ high awning vent.)
- Frame depth is 2-3/4" overall with the nail-on fin located at 7/8" from the exterior.
- Dual glazed windows are glazed with 3/4" overall insulating glass with Intercept™ Warm Edge Technology, providing a minimum of 1/2" air space.
- Surpasses California Model Building Security Ordinance for forced entry requirements.
- Truth hardware with swing cam latch are installed for sure fit and operation. Stainless steel hardware is an available option.
- Thermal ratings as tested with CLIMATE SHIELD™ High Performance Low-E glazing: U-Value = .31 and SHCG = .24 (See *Thermal & Optical Ratings* page for more info).
- Screens are mounted on the inside of the window, with special molded screen corners, concealing corner clips.
- Continuous single finger soft vinyl weather stripping around the frame and vent panel insure air tightness.
- Special sizes upon request.
- Net frame sizes for:
 - Nail-on frame - call out minus 3/8" width and 3/8" height.
 - Block frame - call out minus 1/8" width and 3/8" height.
- Available in White or Almond color.

Configuration Available:

A	=	Single Awning
AA	=	Double Awning
AO/OA	=	Single Awning with Fixed Bottom
TA, TAA, BA, BAA	=	1/2 Awning, 1/2 Fixed